



## Safe-T-First Corner Bumper Guards

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Safe-T-First Corner Bumper Guards

1.2. **Manufacturer:**

Tarkett North America                      Phone: (800) 899-8916  
30000 Aurora Rd.                              (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Vinyl Safe-T-First Corner Bumper Guards are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Safe-T-First Corner Bumper Guards are designed for interior applications only.

1.3.2. **Styles:**

**PVBGN-XX-D (4' or 8'):** 90° angular shaped profile with 2-3/8" (6.03cm) returns. Tapers from 5/16" (7.94mm) at the peak of the nose to 1/16" (1.57mm) at the tip with a co-extruded photoluminescent material.

This product is designed for identifying corners and other pultrusions in the exitway corridor.

1.3.3. **Physical Characteristics:**

Length and Packaging:  
4 ft (1.22m) lengths and 8 ft (2.44 m) lengths - 8 lengths per carton

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1
- **UL 1994 Certified** by Underwriters Laboratories, Inc.

### 3. INSTALLATION

See Safe-T-First Moulding Installation and Maintenance instructions for complete details.

3.1. **Adhesives:**

**Tarkett 946 Premium Contact Adhesive** (Non-porous surfaces)  
Application: Brush  
Approximate coverage:  
1 Quart (0.95 liters) – 24 to 36 sq. ft.  
1 Gallon (3.79 liters) – 100 to 150 sq. ft.

### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

Refer to Tarkett Safe-T-First Resilient Mouldings Installation and maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 800-899-8916.

---

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916 Ext. 9297 Fax 440.632.5643  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)