



Safe-T-First Cove Cap

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

2. **Proprietary Product:** Resilient Safe-T-First Cove Cap Mouldings

1.1. **Manufacturer:**

Tarkett North America Phone (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.2. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett Safe-T-First Cove Cap Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Safe-T-First Cove Cap Mouldings are designed for interior applications only.

1.3.2. **Styles:**

PSCCN-99-B: Resilient Cove Cap - Square top cap for 1/8" (3.18 mm) resilient covered sheet material. Cap extends 1/4" (6.35 mm) over covered material with 3/4" (1.91 cm) glue surface

PCCCN-99-C: Carpet Cove Cap - Square top cap for 1/4" (6.35 mm) covered carpet and wood paneling, 3/8" (9.53 mm) cap extends over covered material with 3/4" (1.91 cm) glue surface.

1.3.3. **Physical Characteristics:**

Length and Packaging:
12 ft. (3.66 m) lengths, 10 pcs per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Fire Resistance** (ASTM E 648/NFPA 253, Critical Radiant Flux):
Class 1

2.2. **UL 1994 Certified** by Underwriters Laboratories, Inc.

3. INSTALLATION

3.1. **Adhesives:**

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

Refer to Tarkett Safe-T-First Resilient Mouldings Installation and maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com