

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** T-Mouldings/Track Bases. Made in USA.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarketta.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett resilient T-Moulding Transitions are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Tarkett transitions are designed for interior applications only.

1.3.2. **Styles:**

T- Mouldings:

CE-XX-A *: 1/4" (6.35mm) and 5/16" (7.94mm) sponge back carpet to 1/8" (3.18mm) resilient, 1-1/16" (2.70cm) cap with 1/4" (6.35mm) long snap-in stem

CE-XX-C *: 1/2" (12.7mm) ceramic to 3/8" (9.53mm) or 1/4" (6.35mm) carpet, 1-5/16" (3.33cm) cap with 1/2" (12.7mm) long snap-in stem

CD-XX *: 1-1/2" (3.81cm) wide level transition for adjoining 1/4" (6.35mm) and 5/16" (7.94mm) carpet, 1/4" (6.35mm) long snap-in stem

CD-XX-A *: 1-1/2" (3.81cm) wide level transition for adjoining 1/2" (12.7mm) materials. 1/2" (12.7mm) long snap-in stem

CD-XX-B: 1/2" (12.7mm) materials to 1/8" (3.18mm) resilient, 1-1/2" (3.81cm) cap with 1/2" (12.7mm) snap-in stem. **Note:** Does not comply with ADA requirements for changes in level.

CD-XX-C *: 3/4" (1.91cm) wide level transition for adjoining 1/4" (6.35mm) and 5/16" (7.94mm) carpet, 1/4" (6.35mm) long snap-in stem

CD-XX-W *: 3" (7.62cm) wide level transition for adjoining 1/4" (6.35mm) and 5/16" (7.94mm) carpet, 1/4" (6.35mm) long snap-in stem

* Complies with ADA requirements for changes in level.

Track Bases:

CDB 00-A: Single Flange Vinyl Track Base for glue down carpet installations.

MT-00-A: Single Flange Aluminum Track Base for glue down carpet installations.

MT-00-B: Single Flange Aluminum Track Base for stretch-in carpet installations.

MTC-00-A: Single Flange Aluminum Contour-able Track Base for glue down carpet installations, 6 ft. minimum bend radius

MTC-00-B: Single Flange Aluminum Contour-able Track Base for stretch-in carpet installations, 6 ft. minimum bend radius

1.3.3. **Physical Characteristics:**

T-Moulding & Track Base Lengths: 12 ft (3.66m)

Packaging:

CDB-00-A - 20 lengths [240 ft. (73.15 m)] per carton

CD-XX-W – 10 pc/carton

All other T-Moulding profiles – 20 lengths per carton

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance** (ASTM D 2047): ≥ 0.5 SCOF

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Tarkett Resilient Moulding installation and maintenance instructions for complete details.

3.2. **Adhesives:**

Tarkett 946 Premium Contact Adhesive (Non-porous surfaces)

Application: Brush on T-moulding and track on mitered corner areas

Approximate coverage:

1 Quart (0.95 liters) – 24 to 36 sq. ft.

1 Gallon (3.79 liters) – 100 to 150 sq. ft.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com