



Tarkett VCT II and Textured Slip Resistant

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Vinyl Composition Tiles designed for durability and commercial interiors.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett VCT II is manufactured from a homogeneous composition of high quality additives, and colorants to meet the performance requirements of ASTM F 1066, Standard Specification for Vinyl composition Tile, Class 2 (Through pattern) and Class 1 (Solid Color).

1.3.2. **Styles:**

- 350002-XXX

1.3.3. **Physical Characteristics:**

- Overall thickness: 1/8" (3.17 mm)
- Size: 12" X 12" (30.5 cm x 30.5 cm)
- Quantity: 45 tiles / carton
- Pallet Quantity: 45 cartons / pallet
- 45 sq. ft. (4.18 m²) / carton
- Weight: 1.4 lbs. / sq. ft. (63 lbs. / carton)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Heat Stability** (ASTM F 1514): $\Delta E \leq 8$
- 2.2. **Size/Squareness** (ASTM F2055): Passes
- 2.3. **Deflection** (ASTM F1304): Passes
- 2.4. **Impact Resistance** (ASTM F1265): Passes
- 2.5. **Dimensional Stability** (ASTM F2199): Passes
- 2.6. **Chemical Resistance** (ASTM F925): Passes
- 2.7. **Static coefficient of friction** (ASTM D 2047): ≥ 0.5 SCOF
- 2.8. **Residual Indentation** (ASTM F1914): Conforms
- 2.9. **Static Load Limit** (ASTM F 970): Passes 150 psi
- 2.10. **Flammability** (ASTM E 648): Class 1

3. INSTALLATION

3.1. See Tarkett Vinyl Composition Tile installation instructions for complete details.

3.2. **Adhesive:**

- **Tarkett 100 Clear Thin Spread Adhesive Coverage:**
Porous & Non-porous Substrate: 250-300 sq. ft./gal.
- **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 901 SpraySmart Adhesive Coverage:**
Porous & Non-porous Substrate: 200 sq. ft. per. container (1,200 sq. ft. per carton)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Vinyl Composition Tile Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com
Contact Technical support at (800)-899-8916 or Email: Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com