

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** High performance recreational commercial sheet flooring; extreme durability combined with easy maintenance. Recommended areas for use:

- Education – Gymnasiums, Sports Halls
- Retail – Sports demonstration areas
- Healthcare – Physical therapy areas

### 1.1. Manufacturer:

Tarkett North America                      Phone:     (800) 899-8916  
30000 Aurora Rd.                                (440) 543-8916  
Solon, Ohio 44139  
Web: www.tarkettna.com

### 1.2. Proprietary Product Description:

**Construction:** Training flooring is composed of a urethane coated clear wearlayer comprised of 90% binder with a thickness of 0.028" (0.7 mm).

#### 1.2.1. Styles:

- Specify TRN-R (Training)

#### 1.2.2. Physical Characteristics:

- Overall thickness is 0.197" (5.0 mm)
- Packaging: Available in 6' 6" (2 m) wide and approximately 67 linear feet (20.5 m) per roll.

### 1.3.1. PRODUCT PERFORMANCE AND TECHNICAL DATA

2. Sheet material meets ASTM F 1303, Type I, Grade 1, Class C performance sheet vinyl floorcovering with backing
- 2.3. **Heat Stability by Color Change** (ASTM F 1514):  $\Delta E \leq 8$
- 2.4. **Light Stability by Color Change** (ASTM F 1515):  $\Delta E \leq 8$
- 2.5. **Flexibility** (ASTM F 137): Passes
- 2.6. **Chemical Resistance** (ASTM F925): Passes
- 2.7. **Static coefficient of friction** (ASTM D 2047):  $\geq 0.5$
- 2.8. **Static Load Limit** (ASTM F 970): 175 psi (< 0.005" residual indentation)
- 2.9. **Fire Performance:** Flooring Radiant Panel: ASTM E 648 – Class 1

## 2. INSTALLATION

See Johnsonite Training installation instructions for complete details.

### 2.1. Adhesives:

- **Johnsonite #925** Adhesive for Resilient Flooring:  
Approximate Coverage:  
Porous & non-porous Substrate: 125-150 sq. ft.
- **Johnsonite #975** Two-Part Polyurethane Adhesive:  
Approximate Coverage:  
Porous & non-porous Substrate: 150-175 sq. ft.

## 3. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 4. WARRANTY

Limited 10 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

## 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Training maintenance instructions for complete maintenance details.

## 6. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.