



# Transcend® Floating Luxury Vinyl Floors

## Product Specification

### 1. PRODUCT DETAILS

- **Nominal Thickness:** 0.158" (4 mm)
- **Wearlayer Thickness:** 0.020" (0.5 mm)
- **Gloss:** Matte Satin
- **Edge Treatment:** Microbeveled

	7.4" x 48" (18.80 x 121.92 cm)	12" x 24" (30.48 x 61 cm)	5" x 37" (12.7 x 94 cm)
<b>Planks / Carton</b>	<b>10</b>	<b>10</b>	<b>15</b>
<b>SQ Feet / Carton</b>	<b>24.03</b> (2.23 m <sup>2</sup> )	<b>19.27</b> (1.80 m <sup>2</sup> )	<b>19.35</b> (1.80 m <sup>2</sup> )
<b>Weight / Carton</b>	<b>42.56 lbs</b> (19.30 kg)	<b>35.64 lbs</b> (16.17 kg)	<b>37.42 lbs.</b> (16.97 kg)
<b>Cartons / Pallet</b>	<b>70</b>	<b>54</b>	<b>63</b>

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Dimensional Stability:** ASTM F2199: Passes
- 2.2. **Heat Stability:** ASTM 1514:  $\Delta E \leq 8$
- 2.3. **Light Stability:** ASTM F1515:  $\Delta E \leq 8$
- 2.4. **Stain Resistance:** ASTM F925: Passes
- 2.5. **Slip Resistance:** ASTM D2047: SCOF  $\geq 0.5$
- 2.6. **Fire Performance:** ASTM E648: Class 1
- 2.7. **Smoke Density:** ASTM E-662: <450
- 2.8. **Static Load Limit:** ASTM F-970: Passes
- 2.9. **FloorScore® Certification:** SCS-EC10.3-2014 v4.0

### 3. INSTALLATION

Refer to Detailed Installation Instructions at [www.tarkettna.com](http://www.tarkettna.com)

- Maintain the work area between 65° F and 85° F (18.3°C - 29.4°C) for 48 hours before and during Installation. Refer to Installation Instructions for complete details regarding applications with and without permanent HVAC controls.
- Cartons shall be stored horizontally on a sturdy base at all times.
- The substrate must be flat within 1/8" in 8 ft and have no more than 1.3mm of deflection.
- Begin installation with the tongue side of the plank facing the starting wall.
- A minimum 1/4" (6.3mm) expansion space is required around the perimeter of the room and all vertical objects.
- Do not use a hammer and tapping block to install Transcend.
- The first and last plank in each row must be at least 12" (30.4cm) in length and offset end joints a minimum of 12" (30.4cm).
- Transcend and ProSheet Plus 3™ is an acceptable installation system. (Follow ProSheet Plus 3 Installation Instructions).
- Transcend and SureStart® Underlayment is an acceptable installation system. (Follow SureStart Underlayment Installation Instructions).

### 4. WARRANTY

For complete details, contact Tarkett Technical Services or go to [www.tarkettna.com](http://www.tarkettna.com)

- LIFETIME EXTREME PERFORMANCE RESIDENTIAL LIMITED WARRANTY
- 10 YEAR LIGHT COMMERCIAL LIMITED WARRANTY

### 5. MAINTENANCE

- 5.1. Furniture can be replaced immediately after installation.
- 5.2. Never slide heavy furniture or appliances across the floor. Place sheets of plywood over finished floor when moving furniture and appliances into position.
- 5.3. Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- 5.4. Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- 5.5. Clean floor using Tarkett SureShine® Floor Cleaner or an equivalent pH neutral floor cleaner. Follow manufacturers label instructions for precaution and use.

### 6. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at (888)-639-8297.



### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
888-639-8275 Fax 440-498-0025  
[northamerican.technicalsupport@tarkett.com](mailto:northamerican.technicalsupport@tarkett.com)

[www.tarkettna.com](http://www.tarkettna.com)