



SureSet™ Luxury Vinyl Flooring Transcend® Collection

Product Specification

1. PRODUCT DETAILS

- **Nominal Thickness:** 0.175" (4.5 mm)
- **Wearlayer Thickness:** 20 mil (0.51 mm)
- **Edge Treatment:** Microbeveled

	6"x36" (15.24 x 91.44cm)	9"x48" (22.86 x 121.92cm)	12"x24" (30.48 x 60.96cm)	12"x36" (30.48 x 91.44cm)
Planks / Carton	10	10	15	8
SQFT / Carton	24.03 (2.23 m ²)	24 (2.23 m ²)	19.35 (1.80 m ²)	24 (2.23 m ²)
Weight / Carton	42.56 lbs (19.30 kg)	35.64 lbs (16.17 kg)	37.42 lbs. (16.97 kg)	40.7 lbs (18.46 kg)
Cartons / Pallet	70	54	63	45

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Dimensional Stability:** ASTM F2199: Passes
- 2.2. **Impact Sound:**
 - **Reduction:** ASTM E2179: ΔIIC 12dB (over 6" Concrete)
 - **Transmission:** ASTM E492: 55 IIC (over Tarkett SureStart Underlayment / 8" Concrete)
- 2.3. **Heat Stability:** ASTM 1514: ΔE ≤ 8
- 2.4. **Light Stability:** ASTM F1515: ΔE ≤ 8
- 2.5. **Stain Resistance:** ASTM F925: Passes
- 2.6. **Slip Resistance:** ASTM D2047: SCOF ≥ 0.5
- 2.7. **Fire Performance:** ASTM E648: Class 1
- 2.8. **Smoke Density:** ASTM E-662: <450
- 2.9. **Static Load Limit:** ASTM F-970: Passes
- 2.10. **FloorScore® Certification:** SCS-EC10.3-2014 v4.0

3. INSTALLATION

Refer to Detailed Installation Instructions at www.tarkettna.com

- Maintain the work area between 65° F and 85° F (18.3°C - 29.4°C) for 48 hours before and during Installation. Refer to Installation Instructions for complete details regarding applications with and without permanent HVAC controls.
- Cartons shall be stored horizontally on a sturdy base at all times.
- The substrate must be flat within 1/8" in 8 ft and have no more than 1.3mm of deflection.
- SureSet and ProSheet Plus 3™ is an acceptable installation system. (Follow ProSheet Plus 3 Installation Instructions).
- SureSet and SureStart® Underlayment is an acceptable installation system. (Follow SureStart Underlayment Installation Instructions).

4. WARRANTY

For complete details, contact Tarkett Technical Services or go to www.tarkettna.com

- LIFETIME EXTREME PERFORMANCE RESIDENTIAL LIMITED WARRANTY
- 10 YEAR LIGHT COMMERCIAL LIMITED WARRANTY

5. MAINTENANCE

- 5.1. Furniture can be replaced immediately after installation.
- 5.2. Never slide heavy furniture or appliances across the floor. Place sheets of plywood over finished floor when moving furniture and appliances into position.
- 5.3. Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- 5.4. Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- 5.5. Clean floor using Tarkett SureShine® Floor Cleaner or an equivalent pH neutral floor cleaner. Follow manufacturers label instructions for precaution and use.

6. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8297.



Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275 Fax 440-498-0025
northamerican.technicalsupport@tarkett.com

www.tarkettna.com