

Face Construction	Imperial	Metric
Construction	Tufted Patterned Symtex®	
Face Weight	26 oz/sq yd	881.4 g/sq m
Gauge	1/10	39.4 rows/10 cm
Stitches per Inch	8.5	33.5 pu/10 cm
Tuft Density	85 tufts/sq in	13.2 tufts/sq cm
Pile Height Average	0.203 inch	5.2 mm
Pile Thickness	0.168 inch	4.3 mm
Density Factor	5,571 oz/cu yd	206.1 kg/cu m
Fiber System	Dyner SD® Nylon (Permanent Stain Resistance)	
Dye Method	Solution Dyed	
Fluorine-Free Soil Protection	Eco-Ensure	7.6 Kilotex
Primary Tufting Substrate	Synthetic Non-Woven	
Pattern Match	Not Required	

Third Party Environmental Certifications

Product	Recycled Content*		NSF 140	Cradle to Cradle
	Overall	Postconsumer	SCS Certified	Certified™ v3.1**
Certified ethos® Modular with Omniccoat Technology™	47-75%	28%	Platinum	Silver

*Minimum recycled content certified by Scientific Certification Systems (SCS) and varies by product style.

**Cradle to Cradle Certified is a certification mark licensed by the Cradle to Cradle Products Innovation Institute.

Product Testing/Information

Antimicrobial Chemicals	No antimicrobials (EPA Registered pesticides) added to product (ASTM E2471-05)
Electrostatic Propensity	1.1 kV (AATCC 134); Permanent Conductive Fiber
Surface Flammability	Passes CPSC FF 1-70 (ASTM D-2859)
Flooring Radiant Panel	Class 1 (mean average CRF: 0.45 w/sq cm or higher) (ASTM E-648)
Smoke Generation	Less than 450 (ASTM E-662)
Colorfastness to Light	≥ 4 after 100 hours (AATCC 16E)
Soil Protection	Application Rate: 2% of Face Weight

Installation Methods

Peel and Stick	RS Adhesive System - Full Coverage Peel & Stick
Wet Spread	Backing specific Tandus Adhesives
Installation Method	Vertical Ashlar; 18" x 36" and 9" x 36" Vertical Ashlar, Herringbone

Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice. Colors may vary slightly from dye lot to dye lot.
- U.S. Patent numbers: 4,849,297; 4,849,267; 5,728,741; 5,855,981; 5,914,353; 6,406,574
- The use of chair pads under roller caster chairs may be required in order to maintain full limited warranty coverage. Please refer to the applicable limited warranty verbiage for specific requirements. In all cases, chair pads are recommended for optimum textural performance. Absent the use of chair pads, more intensive maintenance will be required for areas in direct contact with chair caster traffic, and some degree of appearance change is to be expected.

	IMPERIAL	METRIC	TEST METHOD
--	----------	--------	-------------

Warranty: Lifetime limited warranty against excessive surface wear, static, delamination, edge ravel, zippering & backing resiliency loss. Lifetime limited stain resistance.

ethos® Modular with Omnicoat Technology™

Total Minimum Recycled Content	53.6%			SCS Certified total 47-75%
Pre-Consumer	21.8%			SCS Certified
Postconsumer	31.8%			SCS Certified
Third Party Certification NSF-140	Platinum			SCS Certified
Cradle to Cradle Certification	Silver (Certification #1904)			Cradle to Cradle Certified™ v3.1
Product Size	24" x 24" Tile (18" x 18", 36" x 36". 18" x 36" and 9" x 36" also available)			
Secondary Backing	50% Recycled Content			
Intermediate Layer	Fiberglass Reinforced Sealant			
Product Construction	No Delamination per ASTM D-3936			
Secondary Backing Density	65.0	lbs/cu ft	1041	kg/cu m
Secondary Backing Thickness	0.050	inch	1.3	mm
Total Weight	103.9	oz/sq yd +/-5%	3521.9	g/sq m
CRI Green Label Plus Certification	GLP8320			

