



Tactile Warning

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Tactile Warning A.D.A. and ANSI A117.1, 1986 Compliant

1.1. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.2. **Proprietary Product Description:**

1.2.1. **Construction:** Tarkett Tactile Warning are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants to meet the performance and design requirements of American National Standards Institute (ANSI) A117.1 - 1986, Accessible Warnings on Walking Surfaces to identify open stairwells, platforms, and other hazardous areas. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Tactile Warning are designed for interior applications only and not recommended for commercial kitchen environments.

1.2.2. **Styles:**

- **TW-XX** – Solid Color Tactile Warning Tile
Coils: 12' x 50' x 1/8" (3.66m x 15.24m x 45.72cm)

1.2.3. **Physical Characteristics:**

Packaging - 16 ft² (1.49 m²) per carton. [13.32 lbs. (6.04 kg) per carton]

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- **Hardness** (ASTM D2240): ≥ 85 Shore A
- **Slip Resistance** (ASTM D2047): - ≥ 0.5 SCOF
- **Fire Resistance** (ASTM E648/NFPA 253): ≥ 0.45 W/cm² (Class 1)
- **UL 1994 Certified** by Underwriters Laboratories, Inc.

3. INSTALLATION

See Tactile Warning installation instructions for complete details.

3.1. Adhesives:

- **Tarkett #965** Flooring & Tread Adhesive

Porous Substrates: 1/16" square-notched trowel
(Approximately 125 sq. ft. /gal)

Non-Porous Substrates: 1/16" V-notched trowel
(Approximately 145 sq. ft. /gal)

Important: This adhesive is substrate porosity sensitive. Determine if the substrate is porous or non-porous prior to application of the adhesive and installation of the flooring products and follow the appropriate instructions.

- **Tarkett #996** Two-Part Epoxy Adhesive
Application: 1/16" square notched trowel
(Approximately 150 sq. ft. /gal)
- **Tarkett #975** Two-Part Urethane Adhesive
Application: 1/16" square notched trowel
(Approximately 150 sq. ft. /gal)

Installation Manual: Refer to Tarkett Tactile Warning Installation and Maintenance Instructions for complete installation details.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

Refer to Tarkett Tactile Warning Installation Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com
Contact Technical support at (800)-899-8916 or Email:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 5-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com