

1. PROPRIETARY PRODUCT

Fiberglass reinforced for stability and a polyurethane reinforced finish makes this product durable and easy to maintain.

Recommended areas for use: Residential

2. PRODUCT DETAILS

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** 04000, CH, CP, DW, GC & PO
- **Overall thickness:** .053" (1.4 mm)
- **Wear Layer Thickness:** .010" (0.25 mm)
- **Widths:** 12' (3.6m)
- **Maximum Roll Size:** 205 SY (171 m²)
- **Weight per Square Yard:** 2.40 (1.09 kg)

3. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 3.1. **Sheet Material:** ASTM F 1303, Type I, Grade 3, Class C
- 3.2. **Flooring Radiant Panel:** ASTM E648, >0.45 W/cm²
- 3.3. **Smoke:** ASTM E662, <450
- 3.4. **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness
- 3.5. **FloorScore® Certification SCS-EC10.3-2014:** SCS-FS-02746
- 3.6. **Asthma and Allergy Certified:** Yes

4. ADHESIVE

Tarkett QBond-One Adhesive

Releasable - Medium Nap Roller

Permanent - 1/32" x 1/16" x 1/32" trowel

Tarkett 959 Vinyl Tile and Plank Adhesive

Permanent - Porous: 1/16" x 1/16" x 1/16" V-notch


Non-porous: 1/32" x 1/16" x 1/32" U-notch

Porous/Non-porous: Medium Nap Roller

Follow Instructions on the Adhesive Label.

5. INSTALLATION – Refer to Detailed Instructions at www.tarkettna.com

- Installation System: Floating or Full Spread.
- Maintain the work area, flooring and adhesive between 55° F and 95° F (12.8°C - 35°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One or 959 Vinyl Tile and Plank Adhesive.
- Seal and protect seams from all traffic for a minimum of 3 hours.



6. SEAM METHOD

Glueless-Double-cut dry, use Tarkett S875 Floating Seam Tape under seams on all approved substrates & Tarkett S860 Seam Tape over concrete only.

Full Spread (Releasable) - Double-cut. No tape required.

Full Spread (Permanent) - Double-cut dry. Use Tarkett S860 Seam Tape.

7. SEAM SEALER: Tarkett DT-65 (Low Gloss)

8. WARRANTY – For complete details, contact Tarkett Technical Services or go to www.tarkettna.com

- 5 YEAR LIMITED RESIDENTIAL WARRANTY Material only.

9. CARE AND MAINTENANCE

- When fully adhering, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temp. between 55° F and 95° F (12.8°C - 35°C). Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner.

7. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit www.tarkettna.com or contact Tarkett at (888)-639-8275.