



## Vibe™ FiberFloor® Sheet Flooring

## Product Specifications

### PROPRIETARY PRODUCT

Fiberglass reinforced for stability and a polyurethane reinforced finish makes this product durable and easy to maintain.

**Recommended areas for use:** Residential

### 1. PRODUCT DETAILS

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** M8000
- **Overall thickness:** .125" (3.2 mm)
- **Wear Layer Thickness:** 12 mils
- **Widths:** 12' (3.6m)
- **Maximum Roll Size:** 88 SY (73 m<sup>2</sup>)
- **Weight per Square Yard:** 3.82 (1.73 kg)

### 3. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 3.1. **Flooring Radiant Panel:** ASTM E 648, >0.45 W/cm<sup>2</sup>
- 3.2. **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness
- 3.3. **FloorScore® Certification SCS-EC10.3-2014:** SCS-FS-02746
- 3.4. **Asthma and Allergy Certified:** ASR-1155-03

### 4. ADHESIVE

#### Tarkett QBond-One Adhesive

Releasable - Medium Nap Roller

Permanent - 1/32" x 1/16" x 1/32" trowel

#### Tarkett 959 Vinyl Tile and Plank Adhesive

Permanent - Porous: 1/16" x 1/16" x 1/16" V-notch

Non-porous: 1/32" x 1/16" x 1/32" U-notch

Porous/Non-porous: Medium Nap Roller

**Follow Instructions on the Adhesive Label.**

### 5. INSTALLATION – Refer to Detailed Instructions at [www.tarkettna.com](http://www.tarkettna.com)

- Installation System: Floating or Full Spread.
- Maintain the work area, flooring and adhesive between 55° F and 95° F (12.8°C - 35°C) for 48 hours before, during and after installation. Maintain relative humidity between 40% and 70%.
- Installations subjected to heavy traffic, caster action or requiring net fit must be fully adhered using Tarkett QBond-One or 959 Vinyl Tile and Plank Adhesive.
- Seal and protect seams from all traffic for a minimum of 3 hours.

### 6. SEAM METHOD

**Glueless-Double-cut dry**, use Tarkett S875 Floating Seam Tape under seams on all approved substrates & Tarkett S860 Seam Tape over concrete only.

**Full Spread (Releasable)** - Double-cut. No tape required.

**Full Spread (Permanent)** - Double-cut dry. Use Tarkett S860 Seam Tape.

**SEAM SEALER:** Tarkett DT-65 (Low Gloss)

### 7. WARRANTY – For complete details, contact Tarkett Technical Services or go to [www.tarkettna.com](http://www.tarkettna.com)


- 25 YEAR LIMITED RESIDENTIAL WARRANTY

### 8. CARE AND MAINTENANCE

- When fully adhering, do not replace frequently moved furniture or allow heavy traffic for at least 24 hours.
- Never slide heavy furniture or appliances across the floor. Place sheets of plywood over floor when moving furniture and appliances into position.
- Maintain post installation temp. between 55° F and 95° F (12.8°C - 35°C). Maintain relative humidity between 40% and 70%.
- Use non staining mats or area rugs at doorways and entranceways to collect excess water, sand, grit and debris. Clean the mats and area rugs on a regular basis.
- Use smooth, hard plastic or metal furniture rests or glides under frequently moved furniture to avoid scratches and indentations. Do not use felt pads.
- Wash floor with Tarkett SureShine® Floor Cleaner or equal neutral floor cleaner.

### 9. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at (888)-639-8275.



## Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

888-639-8275 Fax 440-498-0025

[northamerican.technicalsupport@tarkett.com](mailto:northamerican.technicalsupport@tarkett.com)

[www.tarkettna.com](http://www.tarkettna.com)