

Domino & Layer

PRODUCT SPECIFICATION SHEET

Face Construction	Metric	Imperial	Procedure
Construction	Patterned Loop		
Fiber System	100% Nylon		
Dye Method	Solution Dyed		
Gauge	50.4 rows/10cm	5/64	
Stitches per inch	31.0 stitches/10cm	7.9 stitches/inch	ASTM D-418
Pile Height Average	3.8 mm	0.150 inch	ASTM D-418
Density Factor	177.6 kg/m³	4,800 oz/yd³	ASTM D-418

Product Testing Information


Indoor Air Quality	All Tandus Flooring products comply with CRI Green Label Plus Standards ID: #GLP5288.		
	Passes GB 18587-2001		
Surface Flammability	Passes CPSC FF 1-70		ASTM D-2859
Flooring Radiant Panel	Class I (Mean average CRF: 0.45 watts/cm² or higher)		ASTM E-648
Electrostatic Propensity	3.0 kV or lower	Permanent Conductive Fiber	AATCC 134
Colourfastness to Light	≥ 4 after 100 hours		AATCC 16E

Backing System


Standard Backing	Tandus ECOPLY™ PVC Backing
Backing Customization Option	Tandus ECOBOND™ PVC Backing / EcoBase Backing (non-PVC)
Recycled Content	Tandus ECOBOND™ contains a minimum of 35% overall recycled content
Recycling	Recycling 100% recyclable when recovered
Standard Product Size	250 mm x 1000 mm; 500mm x 500mm
Packaging	For Tiles 500x500mm, 1 box (4sqm) includes 16 tiles of each pattern (for accent pattern, all tiles come with accent). For Planks 250x1000 mm, 1 box (4sqm) includes 16 planks of each pattern (for accent pattern, 8 planks come with accent and 8 planks come without accent, as one set includes 1 plank with accent and 1 plank without accent)

Product Notes


- Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature, humidity and colour. Product specifications may vary within normal industry and standardised testing tolerances.
- These specifications reflect mean averages based upon tests of production runs of this carpet style by independent laboratories. A range of variances is implicit in the testing process. Furthermore, the standard test methods established to derive the specifications lack a degree of precision and repeatability; therefore, individual test results on the actual carpet purchased may differ from the specifications above.
- Colours may vary slightly from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements become available which provide for improvement of the product's performance.
- All Tandus Flooring products are 100% recyclable.




QUATER
TURN




VERTICAL
ASHLAR



HORIZONTAL
ASHLAR



VERTICAL
ASHLAR



HERRINGBONE



PHTHALATE
FREE