

iD Elegance Compact 55

TECHNICAL DATA

Classification	Standards	iD Elegance Compact 55
Classification	EN ISO 10582:2010	Heterogeneous PVC Compact floor covering
	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42
Wear Layer binder content	EN ISO 10582	Type I
Technical characteristics		
Total thickness	EN ISO 24346	2,3 mm
Wear layer thickness	EN ISO 24340	0.55 mm
Total weight	EN ISO 23997	3857 g/m²
Bevelled edges	-	No
Surface treatment (PUR)	-	Yes – TopClean XP
Form of delivery	EN ISO 24342	
	Planks	22.86 x 121.92 cm 12 planks / box (3.36m²), 80 boxes/pallet (268.80 m²)
	Tiles	91.44 x 91.44 cm 4 tiles / box (3.34m²), 50 boxes/pallet (167 m²)
Technical performance		
Dimensional stability(%)	EN ISO 23999	≤ 0.25 %
Curl resultant to heat 6h at 80°C (mm)	EN ISO 23999	≤ 2.00 mm
Reaction to fire	EN 13501-1	Bfl-s1 glued over A2fl or A1fl substrate (concrete)
Residual Indentation	EN ISO 24343-1 (EN 433)	Required value: ≤ 0.10 mm Average measured value: 0.03 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 (EN 425)	No damage
Thermal resistance	EN ISO 10456	0.03 m². K/W
Underfloor heating	EN ISO 10456	Suitable – max. 27°C
Impact sound reduction	EN ISO 140-8 EN ISO 717/2	ΔLw = 2 dB
Light fastness	EN ISO 105-B02	≥ 6
Resistance to chemicals	EN ISO 26987 (EN 423)	Good resistance
Slip resistance	DIN 51130 EN 13893	R9
Electrical properties	EN 1815 EN 1081	< 2 kV on concrete R1 > 1010 Ω
Colours	-	Wood: 8 - Ceramic: 3

The above information is subject to modification for the benefit of further improvement.
For the latest information, please visit our website: www.Tarkett-asia.com
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.



RECYCLABLE



PHTHALATE
FREE



≤ 100 µg/m³
OPTIMAL INDOOR
AIR QUALITY

