DESSO Textile floor covering - Broadloom

DESSO & Patricia Urquiola

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10 “						
Aspect	ISO 2424		Structured loop pile						
Dye method			Piece dyed + solution dyed						
Width		cm	400		ft	13.1			
Primary backing	ISO 2424		Polypropylene woven						
Secondary backing	ISO 2424		Polypropylene woven						
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL®**						
Total thickness	ISO 1765	mm	6.6		inch	0.3			
Effective pile thickness	ISO 1766	mm	4.1		inch	0.16			
Total mass	ISO 8543	g/m²	2130		oz/yd²	62.9			
Total pile mass	ISO 2424	g/m²	800		oz/yd²	23.6			
Effective pile mass	ISO 8543	g/m²	510		oz/yd²	15.1			
Pile density	ISO 8543	g/cm³	0.124		lb/in³	0.0045			
Number of tufts	ISO 1763	/dm²	1521		/yd²	127171			
Stroll test	ISO 6356	kV	≤ 2,0						
Vertical resistance	ISO 10965	Ohm	-						
Horizontal resistance	ISO 10965	Ohm	-						
Use classification	EN 1307		23 Domestic - heavy use						
Luxury rating	EN 1307		LC 2						
Impact sound reduction ΔL_w	ISO 10140	dB	-						
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000	
		α_s	-	-	-	-	-	-	
Noise reduction	ISO 354	α_w	-						
Thermal resistance	ISO 8302	m².K/W							
Flammability	EN 13501-1		Cfl - s1 (glued tested)						
Prodis - GUT	www.pro-dis.info								

CE
EN 14041
0493-CPR-0003

Manufactured by:
Tarkett BV
Taxandriaweg 15
NL - 5142 PA Waalwijk

Cfl-s1 DS

23 32

ECONYL® ENDLESS POSSIBILITIES

Quality- and Environmental Management System Certification ISO 9001 & ISO 14001

**ECONYL® is made from 100% regenerated content.

DESSO flooring products are to be installed in full accordance with Tarkett’s installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20250115

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk

Tarkett