

# LAMIN'ART 832 - Chevron

## TECHNICAL DATA LAMINATE

| Classification                          | Norm              | Tarkett Value                                                     |
|-----------------------------------------|-------------------|-------------------------------------------------------------------|
| Product type                            | EN 13329          | Laminate floor covering                                           |
| Class of use                            | EN 13329          | 32                                                                |
| HDF core board density                  | EN 323            | 900 kg/m <sup>3</sup> (± 20 kg/m <sup>3</sup> )                   |
| Locking system                          |                   | UNIFIT®                                                           |
| Technical characteristics               |                   |                                                                   |
| Format                                  |                   | Kingsize                                                          |
| Dimensions                              |                   | 1291 x 327 mm                                                     |
| Complete thickness                      |                   | 8 mm                                                              |
| Bevel                                   |                   | 0V                                                                |
| Performance for CE marking              |                   |                                                                   |
| Declaration of Performance              | EN 14041          | 0132-0078-DoP-2019-06                                             |
| Reaction to fire                        | EN 14041          | Cfl-s1                                                            |
| Slip resistance                         | EN 14041          | DS                                                                |
| Electrostatical propensity              | EN 14041          | < 2 kV                                                            |
| Thermal resistance (in m² K/W)          | EN 14041          | ≤ 0,15 m² K/W                                                     |
| Content of Pentachlorophenol            | EN 14041          | < 5 ppm                                                           |
| Formaldehyde emission                   | EN 14041          | E1                                                                |
| Technical performance                   |                   |                                                                   |
| Abrasion resistance                     | EN 13329, annex E | AC4 (IP ≥ 4000)                                                   |
| Impact resistance                       | EN 13329, annex H | Big ball: ≥ 750 mm      Small ball: ≥ 12 N                        |
| Resistance to staining                  | EN 438            | Group 1 + 2: level 5      Group 3: level 4                        |
| Effect of furniture leg                 | EN 424            | No damage shall be visible, when tested with foot Type 0 artefact |
| Effect of castor chair                  | EN 425 (Type W)   | No change in appearance or damage                                 |
| Thickness swelling                      | ISO 24336         | ≤ 18 %                                                            |
| Tolerance top layer                     | EN 13329          | Length ± 0,5 mm      Width ± 0,1 mm      Thickness ± 0,5 mm       |
| Light fastness                          | EN 13329          | Grey scale ≥ level 4 (EN:20105-A02)                               |
| Static indentation by constant pressure | EN ISO 24343-1    | < 0,05                                                            |
| Surface soundness                       | EN 13329, annex D | ≥ 1,25 N/mm²                                                      |
| Thermal resistance                      | EN 12667          | 0,07 m² K/W                                                       |
| Sustainability & environment            |                   |                                                                   |
| PEFC certification                      |                   | Yes                                                               |
| French VOC rating                       |                   | A+                                                                |
| Emission class for building material    |                   | M1                                                                |
| Carb 2 compliance                       |                   | Yes                                                               |
| Logistics information                   |                   |                                                                   |
| 6 planks/box                            | 2,53 m²/box       | 7,48 kg/m²                                                        |
|                                         |                   | 40 boxes/pallet                                                   |
|                                         |                   | 101,32 m²/pallet                                                  |

The above information is subject to modification for the benefit of further improvement (09/2019)



Download our guarantee conditions from [residential.tarkett.com](http://residential.tarkett.com) or [professionals.tarkett.com](http://professionals.tarkett.com)