

LAMIN'ART 832 - Extra-wide plank

TECHNICAL DATA LAMINATE

Classification	Norm	Tarkett Value
Product type	EN 13329	Laminate floor covering
Class of use	EN 13329	32
HDF core board density	EN 323	900 kg/m ³ (± 20 kg/m ³)
Locking system		UNIFIT®
Technical characteristics		
Format		Kingsize
Dimensions		1291 x 327 mm
Complete thickness		8 mm
Bevel		2V
Performance for CE marking		
Declaration of Performance	EN 14041	0132-0078-DoP-2019-06
Reaction to fire	EN 14041	Cfl-s1
Slip resistance	EN 14041	DS
Electrostatical propensity	EN 14041	< 2 kV
Thermal resistance (in m² K/W)	EN 14041	≤ 0,15 m² K/W
Content of Pentachlorophenol	EN 14041	< 5 ppm
Formaldehyde emission	EN 14041	E1
Technical performance		
Abrasion resistance	EN 13329, annex E	AC4 (IP ≥ 4000)
Impact resistance	EN 13329, annex H	Big ball: ≥ 750 mm Small ball: ≥ 12 N
Resistance to staining	EN 438	Group 1 + 2: level 5 Group 3: level 4
Effect of furniture leg	EN 424	No damage shall be visible, when tested with foot Type 0 artefact
Effect of castor chair	EN 425 (Type W)	No change in appearance or damage
Thickness swelling	ISO 24336	≤ 18 %
Tolerance top layer	EN 13329	Length ± 0,5 mm Width ± 0,1 mm Thickness ± 0,5 mm
Light fastness	EN 13329	Grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure	EN ISO 24343-1	< 0,05
Surface soundness	EN 13329, annex D	≥ 1,25 N/mm²
Thermal resistance	EN 12667	0,07 m² K/W
Sustainability & environment		
PEFC certification		Yes
French VOC rating		A+
Emission class for building material		M1
Carb 2 compliance		Yes
Logistics information		
6 planks/box	2,53 m²/box	7,48 kg/m²
		40 boxes/pallet
		101,32 m²/pallet

The above information is subject to modification for the benefit of further improvement (09/2019)

