

LINOSPORT CLASSIC

Technical data



PROPERTIES	STANDARDS	LINOSPORT CLASSIC
CLASSIFICATION		
Type of floor covering	EN 14041	One single layer calendared linoleum on jute backing
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346 (EN 428)	4mm
Total weight	EN ISO 23997 (EN 430)	ca. 4.7kg/m²
Width	EN ISO 24341 (EN 426)	2m
Length	EN ISO 24341 (EN 426)	ca. 28lm
REQUIREMENTS FOR SAFE USE		
Friction	EN 13036-4	80 to 110
Shock absorption	EN 14808	-
Vertical deformation	EN 14809	-
Specular gloss	EN ISO 2813	≤30%
TECHNICAL PERFORMANCES		
Vertical ball behaviour	EN 12235	
Reaction to fire	EN 13501-1	Cfl-s1*
Resistance to wear	EN ISO 5470-1	-
Resistance to indentation	EN 1516 (Average measured value)	-
Resistance to a rolling load	EN 1569	-
Reduction of impact noise	EN ISO 717-2	-
Thermal resistance	EN ISO 10456	-



* on raw concrete and over Lumaflex sub-constructions

Installation and maintenance guides available on Tarkett Sports Indoor website

Technical data in force as from the date of publication (06/2024).
The values above correspond to laboratory test (no in situ test) and are subject to modifications for the benefit of further improvement.
For more detailed technical information, please contact Tarkett Sports.
Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.