

DATASHEET

Classification		Norm
Product type and classification	EN 16511	Modular mechanical locked floor coverings
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	34 Very Heavy
Technical characteristics		Norm
Total thickness	EN ISO 24337	6.00 mm
Total weight	EN ISO 23997	10.30 kg/m ²
Surface treatment		TEKTANIUM
Bevelled edges		4 sides painted bevel
Installation method		GenClick®
Performance for CE Marking		Norm
Declaration of performance	EN 14041	0197-0070-DoP-2025-03
Wear resistance method A	EN 13329	≥ 2000 cycles
Wear resistance method B	EN 15468	≥ 7000 cycles
Impact resistance	EN 13329	≥ 1800 mm
Micro scratch resistance	EN 16049	MSR-A2
Castor chair resistance	EN ISO 4918	25000
Furniture leg	EN ISO 16581	No visible change
Residual indentation	EN ISO 24343-1	0.02 mm
Resistance to staining	EN 438-2	Groups 1 and 2: grade 5 Group 3: grade 4
Locking strength	ISO 24334	Long side ≥ 2.0 Short side ≥ 3.5
Dimensional stability	EN ISO 23999	Average measured value: ≤ 0.15 %
Curl resultant to heat	EN ISO 23999	≤ 1 mm
Reaction to fire	EN ISO 13501-1	Bfl-s1
Impact sound reduction – ΔLw	EN ISO 717-2	19 dB
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)
Thermal resistance	EN ISO 10456	0.07 m ² • K/W
Colour fastness to light	EN ISO 105-B02	≥ 6
Chemical resistance	EN ISO 26987	Excellent resistance
Slip resistance	DIN 51130 EN 13893	R10 Class DS (μ ≥ 0.30)
Slip resistance – pendulum test	BS 7976	PTV > 36
Under floor heating		Suitable (maximum 27°C)
Sustainability performance		Norm
TVOC emissions after 28 days	EN 16516	Platinum (≤ 10 μg/m ³)
Recyclable through ReStart®		Offcuts and post-use Contact Tarkett for more information
Recycled content	ISO 14021	28%
Carbon footprint (Cradle-to-Gate, EPD Modules A1-A3)		10.90 kg CO ₂ eq/m ²
Total carbon footprint (EPD Modules A-D)		7.39 kg CO ₂ eq/m ²
Phthalate-free		Yes
Dimensions and designs		
Plank (Craft)		1200 × 192 mm – 8 planks = 1.84 m ² /box – 40 boxes/pallet 1500 × 192 mm – 6 planks = 1.73 m ² /box – 44 boxes/pallet
Tile (Elements)		960 × 498 mm – 4 tiles = 1.91 m ² /box – 42 boxes/pallet
Number of designs available		Craft – 12 wood designs Elements – 12 stone designs

The above information is subject to modification for the benefit of further improvement (07/26).
According to the European Regulation N° 305/2011 for CE Marking, the Declarations of Performance are available on our website www.tarkett.com
Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett for these instructions.

