## **GLUE CHART**

## WOOD ACCESSORIES - PRODUCT INFORMATION

## **Recommendations**

Calculated about 1000 g adhesive/ 1 m2  $\pm$  200 g depending on the subfloor.

This chart includes information if MS Primer is needed.

The subfloor must be level, firm, clean, dry and free from dust.

Description	Tarkett Adhesive D	Tarkett Adhesive MS	Tarkett Primer adapted for Adhesive MS
Item code	8790102	8790109	8790108
New concrete, acc to norm	Х	Х	
Old concrete with soft adhesive residues, soft surface		X <sup>1</sup>	1 x (100-150g/m <sup>2</sup> )
Old concrete without old adhesive		X <sup>1</sup>	1 x (100-150g/m <sup>2</sup> )
Old concrete with firm adhesive residues, firm surface		X1	1 x (100-150g/m <sup>2</sup> )
Cement concrete with high moisture, up to 95% RH (6 CM%)		X <sup>2</sup>	2 x (100-150g/layer/m²) Moisture barrier
Underfloor heating, without moisture		Х	
Underfloor heating with high moisture, up to 85% RH (3 CM%)		X <sup>2</sup>	2 x (100-150g/layer/m²) Moisture barrier
Old woodfloor	Х	X <sup>3</sup>	
Chipboard acc to norm, free of dust	Х	Х	
Old chipboard with soft/firm adhesive residues		X <sup>1</sup>	1 x (100-150g/m <sup>2</sup> )
Ceramic tiles		X <sup>3</sup>	

 $X^1$  = On top of one layer of MS Primer.

 $X^2$  = On top of two layer of MS Primer.

X<sup>3</sup> = Remove old layers of cleaning agents, grease, oil etc. Clean the surface thoroughly.

Lacquered surfaces must be sanded before gluing.

Technical Information	Tarkett Adhesive D	Tarkett Adhesive MS	Tarkett Primer adapted for Adhesive MS
Itemcode	8790102	8790109	87090108
Description	Free from organic solvents.	Firm elastic 1-component	1-component primer
Pack size	1 x 14 kg	1 x 18 kg	1 x 11 kg
Installation room temperature	< +18° C	< +15° C	< +18° C
Installation room air humidity	30-60%	30-60%	30-60%
Application rate	700-900 g / m2	800-1400 g / m2	100-150 g / m2 per coat
Container open		max 40 min	
Full adhesion time	24-48 hours	24 hours	24 hours
Storage temperature / time	< +5° C	12 months at 5 to 25°C	12 months at 5 to 20°C

For more information see tarkett.com





