

RAG FELT

WOOD ACCESSORIES - PRODUCT INFORMATION

Cardboard underlay is used as a separating layer in floor constructions. The product has low impact noise insulation. It may be used only on dry subfloors, such as chipboard or old wooden floors. The smooth top surface makes it easier to push the parquet boards together. The product is so thin that it may be an alternative for low overall height and when there is no room for the thicker underlays, (for example under doors). Cardboard underlay is suitable for all types of floating parquet and laminated floors.

Use the chart as a guide to choose correct underlay.
For more exact information contact your floor dealer.

	Pack	Itemcode
Rag felt underlay	15 x 1 m = 15 m ² 63 rolls/box	8790300

Concrete *	Rag felt
Chipboard	
Existing wooden floor	
Underfloor heating *	
* Together with polythene foil	

Composition 100%	
Textile recycled fibre	
Wool	15 %
Cotton	25 %
Wool and cotton waste	8 %
Cellulose recycled pulp	
Cardboard boxes	35 %
Old newspapers	17 %



Technical Information			
Type	Non-impregnated recycled cardboard		
	Unit	Value	
Thickness	mm	0,72	± 4%
Weight	kg/m ²	0,4	± 4%
Resistance to ageing	year	30	(min)
Tensile strength (long)	N/15mm	70	(min)
Tensile strength (cross)	N/15mm	35	(min)
Absorption capacity (DIN 52117)	%	115	± 4%
Water content	%	7	(max)
Thermal resistance Test method EN 13164	m ² Kw ⁻¹	0,013	