

# ROLLER 250

## WOOD ACCESSORIES - PRODUCT INFORMATION

### Tarkett Roller 250

- Easy to use tool for a quick and effective installation for both professional installers and do-it-yourself.
- Roller that applies 250 grams of MS Primer in one application.

Technical Information	Roller 250	
Itemcode	8790215	8790216
Description	Roller 250 with handle for glue down installation	Roller 250 for glue down installation
Pack size	1 x 1	1 x 1
Application rate	250 g/m <sup>2</sup>	250 g/m <sup>2</sup>
For more information see <a href="http://tarkett.com">tarkett.com</a>		

When laying the woodflooring, the relative humidity (RH) in normal structural concrete substrates must not exceed 90% RH. Note that this value applies only to construction moisture and not to moisture addition to floors on the ground, over boiler rooms, with underfloor heating, over high temperature pipes in floors and the like. Please note that measurements should always be carried out by specially trained personnel. As a general rule, vapour barriers should always be used when installing wooden floors on underfloor heating. In the case of organic floor constructions (e.g. wood), there should never be more than one moisture barrier, as moisture can then be trapped between the layers. For these constructions, it is therefore important to check that no moisture protection is already present further down in the construction. The tables below are also applicable for underfloor heating. When gluing to a substrate, wait at least 48-72 hours before the floor can be fully used.

Always refer to the latest installation instructions.

#### 13-22 mm

Subfloor	MS Adhesive	MS Primer
Woodfloor 8-10 % RH	1200 ± 100 g/m <sup>2</sup> <sup>2)</sup>	0 g
Concrete < 65 % RH	1200 ± 100 g/m <sup>2</sup> <sup>2)</sup>	0 g
Concrete 65-85 % RH	1200 ± 100 g/m <sup>2</sup> <sup>2)</sup>	250 g/m <sup>2</sup> <sup>4)</sup>
Concrete 85-90 % RH	1200 ± 100 g/m <sup>2</sup> <sup>2)</sup>	250 g/m <sup>2</sup> <sup>4)</sup>

<sup>2)</sup> Adhesive spreader / trowel TKB B13 (8790211)

<sup>4)</sup> Roller 250 (8790215 / 8790216)

#### Segno

Subfloor	MS Adhesive	MS Primer
Woodfloor 8-10 % RH	800 ± 100 g/m <sup>2</sup> <sup>3)</sup>	0 g
Concrete < 65 % RH	800 ± 100 g/m <sup>2</sup> <sup>3)</sup>	0 g
Concrete 65-85 % RH	800 ± 100 g/m <sup>2</sup> <sup>3)</sup>	250 g/m <sup>2</sup> <sup>4)</sup>
Concrete 85-90 % RH	800 ± 100 g/m <sup>2</sup> <sup>3)</sup>	250 g/m <sup>2</sup> <sup>4)</sup>

<sup>3)</sup> Adhesive spreader / trowel TKB B5 (8790214)

<sup>4)</sup> Roller 250 (8790215 / 8790216)

