

TARKOCLEAN for hardwax oiled floors

WOOD ACCESSORIES - PRODUCT INFORMATION

Tarkoclean for hardwax oiled floors is a highly effective concentrate for everyday cleaning and care.

- Water-soluble concentrate especially developed for oiled and waxed wood floors.
- Used for regular cleaning and care and suitable for both domestic and public spaces.
- Kind to skin, free from pigment and scent, solvent- and emission free and thus healthy living environment.
- Creates a highly effective and easy-to-use surface when used regularly.
- Easy to use and does not leave streaks or traces of excess.
- Suitable also for machine cleaning methods.

Application

- Remove loose dirt by dry mopping, vacuum cleaning or brushing.
- Add Tarkoclean to lukewarm water and clean the floor with a damp mop (not wet!). Use a microfibre mop or flat yarn mop.
- For machine application, spread the diluted Tarkoclean with a pump aerosol can on the floor. Loosen the dirt with a single disc machine and a white pad. Directly remove the loose dirt either manually or with a machine and mop pad
- Do not mix with other cleaners!
- Diluted mixture should be used within 2 weeks!
- Tip: To remove especially tough stains and for periodic maintenance we recommend Tarkett Refresher for hardwax oiled floors. Find our maintenance instructions at tarkett.com



Material no.	8792125
Pack size	1 litre, 6 x 1 litres per box.

Technical Information		
Ingredients	Based on natural plant oils; 5-15% plant soaps (anionic tensides); <5% nonionic tensides; care components, suspending agent.	
Odour	Faint/mild, after drying odourless.	
pH	10,5-11,2 in concentrate, approx 7,5 in standard dilution state.	
Solvent	Water	
Tools	Microfibre mop or flat yarn mop.	
Coverage	1 litre Tarkoclean concentrate gives approx. 135 litres of diluted solution for normal cleaning.	
Mixing ratio	Normal cleaning.	15 ml (1 capful) to 2 litres of water.
	Heavily soiled surfaces or for mechanical application.	Maximum mixing ratio 1:1
Storage time	5 years or longer in unopened container, kept in dry condition and in temperatures between 5 to 30°C.	
Fire hazard	Non-flammable.	
Caution	Keep out of the reach of children. If medical advice is needed, have product container or label at hand. Scan the QR-code for Safety data sheet.	
Contains	5-15% Anionic surfactants, <5% Nonionic surfactants	
Disposal	Dispose of leftover product and empty packaging according to local official guidelines (waste code number 07 06 99). Only completely empty containers can be recycled.	

Hamaskog 2023.10



Scan the QR-code for Safety data sheet.