

#### FOR RESIDENTIAL USE

TECHNICAL DATA (EN 14354)	11 mm					
Reaction to fire	EN 13501	Cfl-s1				
Emission of formaldehyde	EN 14342	E1				
Brinell hardness (average value) Oak	(BHN) EN1534	4,2				
Reduction of sound weighted index $\Delta$ Lw in dB with Tarkett ragfelt $\Delta$ L <sub>w</sub> in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥17 ≥17				
Thermal insulation value (RT m <sup>2</sup> K/W) board only with Tarkett rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,071 0,091 0,111				
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,15				
Construction: softwood veneer and HDF co	3-layer					

INSTALLATION					
Installation method	2-lock for floating				
Installation instruction	Download from www.tarkett.com Contact your supplier for more details				
Underfloor heating compatible Maximum floor surface temperature 27°C with Yes self-regulating underfloor heating system					
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 15 $\ensuremath{m^2}$					

RECOMMENDED ACCESSORIES					
Installation	Tarkofoam II / Tarkoflex II / Tarkett ragfelt / Polythene foil Installation kit				
Aesthetics	Skirting Transition moulding Pipe covers				
Care & Maintenance	Tarkoclean for lacquered floors Refresher for lacquered floors				
See more alternatives and the complete range of accessories @ www.tarkett.com					

#### MAINTENANCE

These Tarkett wooden floors have a surface treatment from Tarkett and therefore a good protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details. Please always refer to maintenance guidance available on websites.

See maintenance instructions @ www.tarkett.com

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel	Character	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Smart Oak White Plank XT	41032002	2 200 x 190 x 11	1-strip	Matt Lacquer	Brushed	2 side minibevel	Expressive	1	0190-0135	1,5	6	2,51	87,85	9,0
Smart Oak White Plank	41033001	2 000 x 162 x 11	1-strip	Matt Lacquer	Brushed	2 side minibevel	Expressive	1	0190-0135	1,5	6	1,94	69,84	9,0
Smart Oak White TreS	41031002	2 281 x 194 x 11	3-strip	Matt Lacquer	Brushed	-	Expressive	1	0190-0135	1,5	6	2,66	93,10	9,0
Smart Oak Plank XT	41032001	2 200 x 190 x 11	1-strip	Matt Lacquer	Brushed	2 side minibevel	Expressive	1	0190-0135	1,5	6	2,51	87,85	9,0
Smart Oak TreS	41031001	2 281 x 194 x 11	3-strip	Matt Lacquer	Brushed	-	Expressive	1	0190-0135	1,5	6	2,66	93,10	9,0
Smart Oak Light Brown Plank XT	41032003	2 200 x 190 x 11	1-strip	Matt Lacquer	Brushed	2 side minibevel	Expressive	1	0190-0135	1,5	6	2,51	87,85	9,0
Due to the nature of the material this table shows typical values														

Due to the nature of the material this table shows typical values

1: Quercus Robur & Quercus Petraea







Hanaskog 2024.01

# **SMART** OAK WHITE PLANK XT - 41032002



Smart products have all the natural variations in structure and colour, from light to dark, and can include sapwood and knots without limitations. Knots and cracks are often filled or partially filled with dark putty. Tiny cracks and holes without putty can be found occasionally. The proportion of knots and sapwood will vary between batches. To get an overall impression of potential variations, see also images of other Smart products. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks.



When sanding a wooden floor the appearance will change in colour, texture and surface effects.

# **SMART** OAK WHITE PLANK - 41033001













# **SMART** OAK WHITE TRES - 41031002













#### **SMART** OAK PLANK XT - 41032001













#### **SMART** OAK TRES - 41031001













# **SMART** OAK LIGHT BROWN PLANK XT - 41032003



