

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	Desso BV
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-DES-20160158-CAB1-DE
Issue date	30.09.2016
Valid to	29.09.2021

Tufted carpet tiles

Pile material 800-900 g/m² polyamide 6 with 0% recycled content and EcoBase™ backing

www.ibu-epd.com / <https://epd-online.com>



General Information

Desso BV, a Tarkett company
www.desso.com

Programme holder

IBU - Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Declaration number

EPD-DES-20160158-CAB1-DE

This Declaration is based on the Product Category Rules:

Floor coverings, 07.2014
(PCR tested and approved by the SVR)

Issue date

30.09.2016

Valid to

29.09.2021



Prof. Dr.-Ing. Horst J. Bossenmayer
(President of Institut Bauen und Umwelt e.V.)



Dr. Burkhard Lehmann
(Managing Director IBU)

Tufted carpet tiles
Pile material 800-900 g/m² PA 6 with
0% recycled content and
EcoBase™ backing.

Owner of the Declaration

Desso BV
Taxandriaweg 15
5142 PA Waalwijk
The Netherlands

Declared product / Declared unit

1 m² Tufted carpet tiles Pile material 800-900 g/m² PA 6 with 0% recycled content and EcoBase™ backing.

Scope:

The declaration applies for a group of tufted modular carpet tiles.

It is only valid in conjunction with a valid PRODIS licence.

The products are produced in the manufacturing sites Dendermonde, Belgium (tufting) and in Waalwijk, the Netherlands (precoating and heavy coating). The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Verification

The CEN Norm /EN 15804/ serves as the core PCR

Independent verification of the declaration
according to /ISO 14025/

internally externally



Dr. Eva Schmincke
(Independent verifier appointed by SVR)

Product

Product description

Product description

Tufted carpet tiles with a surface pile of 0% recycled solution-dyed polyamide 6 and a DESSO EcoBase® backing. The declaration applies for a group of products with a total pile-material of 800-900 g/m². The calculations refer to the average pile-material input of 850 g/m².

DESSO EcoBase® Backing

DESSO EcoBase® is a polyolefin based backing which contains 100% positively defined* recycled calcium carbonate (chalk) as well as a polypropylene covering fleece and glass scrim reinforcement. The EcoBase™ backing is 100% recyclable in Desso's own production process. Products declared in this EPD have a minimum of 40% positively defined* recycled content.

Application

According to the use class as defined in /EN 1307/ the products can be used in all professional area which require **class 33** or less.

Technical Data

Name	Value	Unit
Product form	Tiles	-
Type of manufacture	Tufted	-
Yarn type	0% recycled PA6	-
Total carpet weight	4400	g/m ²
Surface pile weight	800 - 900	g/m ²
Secondary backing	EcoBase™ backing	-

Additional product properties according to /EN 1307/ can be found on the "Product Information System" (PRODIS) using the PRODIS registration number of the product. www.pro-dis.info or on the Desso website: www.desso.com

Base materials / Ancillary materials

Name	Value	Unit
Polyamide 6	19.1	%
Polyester	2.3	%
Polypropylene	1.0	%
Calcium Carbonate (chalk)	51.6	%
Polyolefin	17.1	%
Aluminium tri hydrate	3.9	%
Latex	3.9	%
Glass fibre	0.6	%
additives	0.6	%

Reference service life

The service life of textile floorcoverings strongly depends on the correct installation taking into account the declared use classification and the adherence of cleaning and maintenance instructions. A minimum service life of 10 years could be assumed, technical service life can be considerably longer.

*Positively defined = all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® CertifiedCM Product Standard Version 3.1.

LCA: Calculation rules

Declared Unit

Declared unit

Name	Value	Unit
Declared unit	1	m ²
Conversion factor to 1 kg	0.237	-
Mass reference (average product)	4.4	kg/m ²

Database: EcolInvent

System boundary

Type of the EPD: Cradle-to-grave.

System boundaries of the modules A, B, C, D:

A1-A3 Production:

Energy provision, production of raw material that is not secondary material (e.g. additives, dyes), yarn processing (e.g. solution dyeing):

Auxiliary material, transport of any material to the manufacturing site, waste water treatment, production of packaging material and waste processing of residual waste up to the landfill. Credits for electricity and steam from the incineration of production waste are not taken into account nor are any credits as a result of carbon offsetting.

A4 Transport:

Transport of the packed textile floor covering from manufacturing gate to the place of installation.

A5 Installation:

Installation of the textile floor covering, production and transport of auxiliary material, waste processing up to the landfill of residual waste, the production of the amount of carpet that occurs as installation waste incl. its transport to the place of installation.

Credits for electricity and steam from the incineration of installation waste leave the product system and are not declared in Module D.

B1 Use:

Product related VOC-emissions are not relevant.

B2 Maintenance:

Cleaning of the textile floor covering for a period of 1 year:

- Vacuum cleaning – electricity supply
- Wet cleaning – electricity, water consumption, production of the cleaning agent, waste water

treatment.

The declared values in this module have to be multiplied with the assumed service time of the floor covering in the building in question.

B3 - B7:

The modules are not relevant and therefore not declared.

C1 De-construction:

De-construction of the floor covering is made by handcraft and causes no additional impacts.

C2 Transport:

Carpet waste is returned to Desso and therefore the distance is equal to the impact in A4.

C3 Waste processing:

The yarn is separated from the backing. The carpet tile is processed at Desso. Desso specific data is used as input for this module.

C4 Disposal

Non-recycled waste is discarded by Desso for use in the cement industry. Potential benefits are allocated to module D.

D Recycling Potential:

The EcoBase™ backing is 100% recyclable in Desso's own production process and therefore replaces primary EcoBase™ in the carpet tile production. The yarn is extracted from the tile and sent for recycling to create new yarn. Polyester tuft cloth and latex compound are used as fuels in the cement production. D/1 is the recycling potential of EcoBase™ carpet tile backing.

D/2 is the recycling potential of PA6.

D/3 are the benefits from substituting fuel in the cement production.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

Transport to the construction site (A4)

Name	Value	Unit
Litres of fuel	29.4	l/100km
Transport distance	700	km
Capacity utilisation (including empty runs)	85	%
Gross density of products transported	700	kg/m ³

Installation in the building (A5)

Name	Value	Unit
Auxiliary	0.2	kg
Material loss	0.13	kg

Cardboard waste (packaging material) leaves the system for recycling. Installation waste is considered to be incinerated in a municipal waste incineration plant.

Maintenance (B2)

Name	Value	Unit
Maintenance cycle (wet cleaning)	1.5	1/year
Cleaning agent (wet cleaning)	0.06	kg/year
Water consumption (wet cleaning)	0.03	m ³
Maintenance (dry cleaning)	208	1/year
Electricity consumption	0.314	kWh

Further information on cleaning and maintenance see www.desso.com

End of Life (C1-C4)

DESSO EcoBase® products are designed for disassembly and recycling. Next to that a Take Back programme has been put in place as well as a recycling facility called Refinity®. Removal of used carpet tiles is done by hand and the reverse logistic process is organised by Desso.

In order to further secure the return of these valuable raw materials, Desso has also launched a Carpet Lease™ programme together with global financial solutions provider DLL.

Name	Value	Unit
Collected separately	4.4	kg
Recycling	4.4	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Both the yarn and EcoBase™ backing can be recycled. The backing can be used 100% in Desso's own production process. After additional processing, the yarn (PA6) can be used as yarn again. This means that both materials replace the need for primary materials in the next phase. Polyester and latex compound are used as fuels in the production of cement.

Name	Value	Unit
DESSO Ecobase® recovered of total tile	58.6	%
Polyamide 6 recovered of total tile	19.1	%
Calcium Carbonate (chalk)	9.5	%
Polyester, Latex, Energy recovery	12.8	%

Recycling in the cement industry: the organic material of the carpet is used as secondary fuel in a cement kiln. It substitutes mainly lignite (58%), hard coal (26%) and petrol coke (12%). The inorganic material is substantially integrated in the cement clinker and substitutes virgin material input.

LCA: Results

Modules B3 - B7 are not relevant during the service time of the carpet and are therefore not declared. Module C1 causes no additional impact (see "LCA: Calculation rules", "C1 De-construction") and is therefore not declared. The declared values in module B2 have to be multiplied with the assumed service time (in years) of the floor covering in the building considered.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	MND	MND	MND	MND	MND	MND	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1m² EcoBase™ carpet tiles - 800 to 900 g/m² PA6, 0% recycled

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3	C4	D/1	D/2	D/3
GWP	[kg CO ₂ -Eq.]	1.27E+1	5.32E-1	3.33E-1	0.00E+0	2.47E-1	5.32E-1	1.86E-2	0.00E+0	-2.13E+0	-5.73E+0	-8.34E-2
ODP	[kg CFC11-Eq.]	3.23E-7	9.73E-8	2.89E-8	0.00E+0	5.60E-8	9.73E-8	6.72E-10	0.00E+0	-2.31E-8	-2.04E-9	-2.81E-8
AP	[kg SO ₂ -Eq.]	4.30E-2	2.15E-3	1.05E-3	0.00E+0	1.82E-3	2.15E-3	2.25E-5	0.00E+0	-4.68E-3	-1.83E-2	-7.11E-4
EP	[kg (PO ₄) ³⁻ -Eq.]	1.16E-2	4.62E-4	7.68E-4	0.00E+0	8.59E-5	4.62E-4	7.59E-6	0.00E+0	-1.45E-3	-4.12E-3	-7.04E-5
POCP	[kg ethene-Eq.]	2.19E-3	9.08E-5	3.26E-4	0.00E+0	8.26E-5	9.08E-5	1.13E-6	0.00E+0	-4.23E-4	-8.37E-4	-4.05E-5
ADPE	[kg Sb-Eq.]	7.97E-2	3.88E-3	1.43E-3	0.00E+0	3.15E-4	3.88E-3	1.40E-5	0.00E+0	-8.82E-3	-3.43E-2	-7.19E-3
ADPF	[MJ]	2.01E+2	8.49E+0	9.01E-1	0.00E+0	5.37E+0	8.49E+0	4.43E-3	0.00E+0	-3.53E+1	-1.74E-1	-9.77E+0

Caption: GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

RESULTS OF THE LCA - RESOURCE USE: 1m² EcoBase™ carpet tiles - 800 to 900 g/m² PA6, 0% recycled

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3	C4	D/1	D/2	D/3
PERE	[MJ]	7.19E+0	1.01E-1	1.19E+0	0.00E+0	3.40E-1	1.01E-1	3.00E-1	0.00E+0	-2.97E-1	-3.46E-1	-1.90E-2
PERM	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	[MJ]	7.19E+0	1.01E-1	1.19E+0	0.00E+0	3.42E-1	1.01E-1	3.00E-1	0.00E+0	-2.97E-1	-3.46E-1	-1.90E-2
PENRE	[MJ]	2.19E+2	8.63E+0	3.81E+0	0.00E+0	4.89E+0	8.63E+0	2.91E-2	0.00E+0	-6.03E+1	-7.50E+1	-1.28E+1
PENRM	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PENRT	[MJ]	2.19E+2	8.63E+0	3.81E+0	0.00E+0	4.91E+0	8.63E+0	2.37E-1	0.00E+0	-6.03E+1	-7.50E+1	-1.28E+1
SM	[kg]	1.78E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	-1.80E+0	0.00E+0	0.00E+0
RSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	[m ³]	1.28E-2	4.75E-4	2.31E-2	0.00E+0	9.85E-3	4.75E-4	2.55E-5	0.00E+0	1.90E-4	2.22E-3	-3.82E-5

Caption: PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

1m² EcoBase™ carpet tiles - 800 to 900 g/m² PA6, 0% recycled

Parameter	Unit	A1-A3	A4	A5	B1	B2	C2	C3	C4	D/1	D/2	D/3
HWD	[kg]	6.16E-5	4.82E-6	3.52E-3	0.00E+0	1.75E-1	4.82E-6	1.60E-2	0.00E+0	-7.33E-6	-7.13E-7	-1.15E-6
NHWD	[kg]	6.08E-1	3.78E-1	3.83E-2	0.00E+0	9.43E-1	3.78E-1	3.35E-3	0.00E+0	-1.16E-2	-5.01E-2	-8.75E+0
RWD	[kg]	1.96E-4	5.51E-5	3.51E-3	0.00E+0	1.75E-1	5.51E-5	1.58E-2	0.00E+0	-4.41E-6	-5.51E-7	-8.62E-7
CRU	[kg]	0.00E+0	0.00E+0	2.37E-5	0.00E+0	1.18E-3	0.00E+0	1.98E-5	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MER	[kg]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EEE	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	[MJ]	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0

Caption: HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EEE = Exported thermal energy

Interpretation

In order to understand the full environmental impact of products declared in this EPD, one should consider Module D when comparing on building level.

This product is specifically designed for recycling, which is demonstrated in Module D.

References

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.):
Generation of Environmental Product Declarations
(EPDs);
www.ibu-epd.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and
declarations — Type III environmental declarations —
Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of
construction works — Environmental Product
Declarations — Core rules for the product category of
construction products

PCR 2011, Part B

Institut Bauen und Umwelt e.V., Königswinter (pub.):
Product Category Rules for Construction Products
from the range of Environmental Product Declarations
of Institut Bauen und Umwelt (IBU),
Part B: Requirements on the EPD for floor coverings,
June 2011
www.bau-umwelt.de

EN 1307

DIN EN1007:Textile floorcoverings - Classification of
pile carpets, 20008-8

EN 14041

DIN EN 14041: 2008-05: Resilient, textile and laminate
floor coverings

ISO 10874

DIN EN ISO 10874: 2012-04: Resilient, textile and
laminate floor coverings - Classification

EN 13501-1

DIN EN 13501-1: 2010-01: Fire classification of
construction products and building elements - Part 1:
Classification using data from reaction to fire tests.

Cradle to Cradle®

Cradle to Cradle CertifiedCM Product Standard
Version 3.1 McDonough Braungart Design Chemistry
(MBDC) 2016.

**Publisher**

Institut Bauen und Umwelt e.V.
Panoramastr. 1
10178 Berlin
Germany

Tel +49 (0)30 3087748- 0
Fax +49 (0)30 3087748- 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

**Programme holder**

Institut Bauen und Umwelt e.V.
Panoramastr 1
10178 Berlin
Germany

Tel +49 (0)30 - 3087748- 0
Fax +49 (0)30 – 3087748 - 29
Mail info@ibu-epd.com
Web www.ibu-epd.com

Logo

Author of the Life Cycle Assessment

Name
Straße, Nr.
PLZ, Ort
Land

Tel Nummer
Fax Nummer
Mail e-mail
Web **Web-Adresse**



A Tarkett Company

THE ULTIMATE
FLOORING EXPERIENCE

Owner of the Declaration

Desso BV
Taxandriaweg 15
5142PA Waalwijk
Netherlands

Tel +31(0)416684100
Fax +31(0)416335955
Mail info@desso.com
Web www.desso.com