

ICONIK 260

Green Building Card



SUSTAINABILITY ATTRIBUTES

Circular Economy and Climate Change



Good Materials



Indoor Air Quality



This product's installation waste is recyclable in our recycling centres



CONTRIBUTION TO GREEN BUILDING CERTIFICATIONS

BREEAM®

BREEAM INTERNATIONAL NEW CONSTRUCTION 2016

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
HEA 01 - Visual Comfort	Best practices in daylighting and artificial lighting design <i>No specific requirement at product level</i>	
HEA 02 - Indoor Air Quality	TVOC at 28 days $\leq 1000 \mu\text{g}/\text{m}^3$ and Formaldehyde at 28 days $\leq 60 \mu\text{g}/\text{m}^3$	  
MAT 03 - Responsible Sourcing of Construction Products	ISO 14001 certified	
MAT 06 - Material Efficiency	Ingredients verified by a third party or Product composed of recycled content	 
WST 01 - Waste Management	Avoid sending waste to landfill <i>No specific requirement at product level</i>	 

LEED v4.1 Building Design and Construction

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
MR - Sourcing of Raw Materials	Signatory of the UN Global Compact or Product composed of recycled content or Recyclable at end-of-life or Bio-sourced materials	 
MR - Material Ingredients	Ingredients verified by a third party or Cradle to Cradle® certification at bronze level or higher	
MR - Construction and Demolition Waste Management	Avoid sending waste to landfill <i>No specific requirement at product level</i>	 
EQ - Low Emitting Materials and Indoor Air Quality Assessment	TVOC at 28 days $\leq 1000 \mu\text{g}/\text{m}^3$ and Formaldehyde at 28 days $\leq 10 \mu\text{g}/\text{m}^3$ Decrease the concentration of particles in the air	  
EQ - Interior Lighting and Daylight	Best practices in daylighting and artificial lighting design <i>No specific requirement at product level</i>	

CONTRIBUTION TO GREEN BUILDING CERTIFICATIONS



WELL BUILDING STANDARD v2

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
L02 - Visual Lighting Design and L 06 - Daylight Simulation	Best practices in daylighting and artificial lighting design <i>No specific requirement at product level</i>	 VISUAL COMFORT
S07 - Impact Noise Management	Best practices in impact noise reduction- <i>No specific requirement at product level</i>	 20dB IMPACT NOISE REDUCTION
X01, X02 and X05 - Material Restrictions, Interior Hazardous Materials Management and Enhanced Material Restrictions	Asbestos < 1000 ppm Halogenated flame retardants < 100 ppm PFAS < 100 ppm Lead < 100 ppm Cadmium < 100 ppm Mercury < 100 ppm Orthophthalates < 100 ppm <i>Higher amounts are allowed if required by local code</i>	 Verify compliance according to chemicals displayed in MHS. Evaluation threshold at least 100 ppm (0.01%) of the final product.
X06 - VOC Restrictions	TVOC at 28 days ≤ 1000 µg/m ³ and Formaldehyde at 28 days ≤ 124 µg/m ³ (E1)	  
X07 - Materials Transparency	Ingredients verified by a third party or Cradle to Cradle® certification at bronze level or higher	
X08 - Materials Optimization	Ingredients verified by a third party or Cradle to Cradle® certification at silver level or higher	

SKA RATING OFFICES 1.2



CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Reduce floor finishes sent to landfill	Avoid sending waste to landfill <i>No specific requirement at product level</i>	 
Low VOC finishes	TVOC at 28 days ≤ 100 µg/m ³ and Formaldehyde at 28 days ≤ 10 µg/m ³ or Ingredient disclosure	  
Daylighting	Best practices in daylighting design <i>No specific requirement at product level</i>	 VISUAL COMFORT



CONTRIBUTION TO GREEN BUILDING CERTIFICATIONS



DGNB System - New buildings Version 2020 International

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
ENV1.2 - Local Environment Impact	Textile flooring - Quality level 4 TVOC at 28 days $\leq 100 \mu\text{g}/\text{m}^3$ SVHC $< 0,1\%$ Biocidal products only in accordance with 528/2012/EC Resilient flooring - Quality level 4 TVOC at 28 days $\leq 300 \mu\text{g}/\text{m}^3$ SVHC $< 0,1\%$ Chlorinated paraffins $< 0,1\%$ Phthalates that are toxic to reproduction $< 0,1\%$ No use of lead and cadmium compounds	  Verify compliance according to chemicals displayed in MHS. Evaluation threshold at least 100 ppm (0.01%) of the final product. Manufacturer declaration may also be provided - contact TARKETT's sales representative.
ENV1.3 - Sustainable Resource Extraction	Product composed of open-loop or post-consumer recycled content	
SOC1.2 - Indoor Air Quality	Indoor air quality measurement after construction work No specific requirement at product level	 
SOC1.3 - Acoustic Comfort	Best practices in impact noise reduction- No specific requirement at product level	
SOC1.4 - Visual Comfort	Best practices in daylighting and artificial lighting design No specific requirement at product level	
TEC1.6 - Ease of Recovering and Recycling	Efficient use of resources	 

NF HABITAT HQE V4.1



CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Qualité de l'air intérieur	Etiquetage sanitaire français	  
Confort Visuel	Bonnes pratiques sur l'éclairage naturel et artificiel- Pas d'exigence spécifique au niveau des produits	
Déchets	Eviter l'envoi à la décharge Pas d'exigence spécifique au niveau des produits	 



CONTRIBUTION TO GREEN BUILDING CERTIFICATIONS



HOME QUALITY MARK

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
4.1 Indoor Pollutants	TVOC at 28 days $\leq 1000 \mu\text{g}/\text{m}^3$ and Formaldehyde at 28 days $\leq 60 \mu\text{g}/\text{m}^3$	 <10 $\mu\text{g}/\text{m}^3$ LOW FORMALDEHYDE EMISSIONS  <100 $\mu\text{g}/\text{m}^3$ OPTIMAL INDOOR AIR QUALITY
4.2 Daylight	Best practices in daylighting and artificial lighting design <i>No specific requirement at product level</i>	 VISUAL COMFORT
4.4 Sound Isolation	Best practices in impact noise reduction <i>No specific requirement at product level</i>	 20dB IMPACT NOISE REDUCTION
6.1 Responsible Sourcing	Ingredients verified by a third party or- Product composed of recycled content and ISO 14001 certified	 MHS MATERIAL · HEALTH · STATEMENT  Tarkett ISO 14001 ENVIRONMENTAL MANAGEMENT SYSTEM  20% RECYCLED CONTENT
10.4 Site Waste Management	Avoid sending waste to landfill <i>No specific requirement at product level</i>	 RECYCLABLE OFFCUTS & POST-USE  Restart Ready

HQE BÂTIMENT DURABLE v4

CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Qualité de l'air intérieur	Mesure de polluants dans l'air après travaux	 A+  <10 $\mu\text{g}/\text{m}^3$ LOW FORMALDEHYDE EMISSIONS  <100 $\mu\text{g}/\text{m}^3$ OPTIMAL INDOOR AIR QUALITY
Confort Visuel	Bonnes pratiques sur l'éclairage naturel et artificiel <i>Pas d'exigence spécifique au niveau des produits</i>	 VISUAL COMFORT
Déchets	Envier l'envoi à la décharge <i>Pas d'exigence spécifique au niveau des produits</i>	 RECYCLABLE OFFCUTS & POST-USE  Restart Ready
Economie locale	Composant issu d'une filière de valorisation matière des déchets	 20% RECYCLED CONTENT



CONTRIBUTION TO GREEN BUILDING CERTIFICATIONS

Green Star - Interiors v1.3



CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Indoor Pollutants	TVOC at 28 days $\leq 1000 \mu\text{g}/\text{m}^3$ and Formaldehyde at 28 days $\leq 10 \mu\text{g}/\text{m}^3$	 
Lighting and Visual Comfort	Best practices in daylighting and artificial lighting design <i>No specific requirement at product level</i>	
Construction and Demolition Waste	Avoid sending waste to landfill <i>No specific requirement at product level</i>	 

MILJÖBYGGNAD



CERTIFICATION CRITERIA	CERTIFICATION REQUIREMENTS	THE TARKETT RESPONSE
Indicator 13 (V3.0 & 3.1) Indicator 15 (V4.0)	Composition declared according to CLP/REACH None classified compounds are publicly declared if they make up >2% of composition	 See available eBVD for Swedish adaptation.
Indicator 14 (V3.0 & 3.1) Indicator 9 (V4.0)	Hazardous classified below CLP guidelines TVOC at 28 days $\leq 1000 \mu\text{g}/\text{m}^3$ Formaldehyde at 28 days $\leq 10 \mu\text{g}/\text{m}^3$	   See available eBVD for Swedish adaptation.
Indicator 13 (V4.0)	At least 20% recycled content	