

CARE AND MAINTENANCE



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE

FiberFloor®

It's Nice to Look Amazing with So Little Effort.

March 20, 2017

CARE AND MAINTENANCE

To ensure the best performance and quality of your new floor follow these basic steps:

- Replace furniture and refrain from heavy traffic for 24 hours after installation in fully adhered applications. Protect sealed seams for 24 hours after application.
- When moving heavy furniture or appliances, use extreme caution and move using plywood or hardwood panels to avoid damage.
- Full adhesion is recommended for commercial applications and in residential applications where rolling carts or wheel chairs are present.
- Use proper rests, glides and casters on furniture as the recommended stationary load is 75 lbs per square inch. Small narrow furniture rests should be replaced with wider, smooth, non-staining, protective load-bearing devices (at least 1" square or 1-1/8" diameter per 50-75lbs).
- Do not walk on the floor with narrow-heeled shoes which will cause permanent indentation that is not covered under the warranty.
- Close drapes or blinds to minimize the repeated sunlight exposure and to minimize fading, bleaching and discoloration.
- Select area rugs/mats carefully to avoid staining from rubber backings and dyes.
- Protect the floor against heat emissions from refrigerators and other appliances by keeping them clean and free of dust around motors and exhaust areas. The airflow of forced-air heating systems should be directed away from the floor. Over time heat will cause discoloration.
- Tarkett FiberFloor requires little maintenance and should be sweep/vacuumed regularly followed by routine cleaning with water and a neutral cleaner. To minimize damage to the floor, immediately treat all stains and spills.
- Visit TarkettNA.com/resources for installation directions and for information on treating stains, warranties, and detailed clean, care and maintenance instructions.



Tarkett

THE ULTIMATE
FLOORING EXPERIENCE