

Lumaflex Evolution

LINOSPORT XF²

Maintenance instructions

October 2021

Linospport xf² has a factory-applied surface coating called xf². This makes Linospport xf² extremely resistant to abrasion, stains and chemicals and thus makes it easier to maintain. This product does not require metallization or a coating of any sort of wax before traffic can circulate on it.

Please note that to provide the end-customer with the best use of the flooring, the maintenance procedure must carefully be followed. If not, Tarkett Sports will decline all potential damages following a non appropriate maintenance procedure.



**After installation, ensure that the temperature is always maintained between 15 and 28°C
Relative air rate moisture must be maintained between 35 and 65%.**

GENERAL ADVICES :

Anyone using the sports surface must wear dedicated footwear, suitable and specific for practicing indoor sports. Around 80% of dust are coming from outside, doormats should be installed at the entrance of the sports hall which include :

A rubber or brush mat to remove coarse dirt,
A ribbed carpet mat to retain fine and damp dirt,
A carpet mat to absorb residual moisture and dirt.



Minimum 5 "foot sweeps" is recommended

Emco : www.emco-bau.com

DAILY MANUAL MAINTENANCE :

Remove dust and gravels by sweeping or vacuum cleaning.



WEEKLY MECHANICAL MAINTENANCE :

Minimum once a week, wash mechanically with an automatic scrubber machine (for example Nilfisk BR652) fitted out with 3M red pads or with an auto scrubber (for example Rotowash B60) equipped with flexible grey brushes. Dilute the cleaning product (such as Dynatech Clean Force Orange) by 1% (100 ml for 10 L) in the tank.

Dynatech (Werner et Mertz) : www.wmprof.com

Rotowash : www.rotowash.com

Nilfisk : www.nilfisk.com



Important: Please follow manufacturer's recommendations.

If any doubts, please contact your local Tarkett Sports representative for further information.



Lumaflex Evolution

LINOSPORT XF²

Maintenance instructions

October 2021

PERIODICAL MAINTENANCE :

A periodical care can be done by using an automatic scrubber machine (for example Nilfisk BR652) fitted out with 3M red pads or with an auto scrubber (for example Rotowash B60) equipped with flexible grey brushes.

Dilute the cleaning product (such as Tanex Trophy) by 10%. Apply the mix (water/Tanex Trophy) without vacuuming. Let the product soak into the floor for 5 minutes, vacuum the surface, and then clean against the floor only with water.

Important: Please follow manufacturer's recommendations.

For this periodical maintenance, you can also use a special scrub disc to avoid using detergent.

ADN company : www.adnnord.net



STAINS REMOVAL :

Spills should be wiped up quickly, by using a white clean cloth, before they have time to set, then clean the floor with clear water.

For stubborn stains on the floor (handball players resin for instance), spray Tanex Trophy (dilution 20%), let it work during 1 minute, rub with a piece of 3M pad red, flush with water and sweep with a white clean cloth.

Important: Please follow manufacturer's recommendations.



CAUTION, DO NOT USE :

Benzene, toluol, acetone, tetrachlororoethene, thinner, oil wax or strong scouring powders.....

Black rubber tires (pad on the feet of seats, bench.....) can cause permanent discoloration and should not be used.

The information given in this guide is provided for indicative purposes only. It is the result of our knowledge and our experience. It shall be taken as general maintenance instructions and cannot, by definition, incorporate the actual data for each installation. We therefore reserve the right to modify it at any time.

If any doubts, please contact your local Tarkett Sports representative for further information.



Lumaflex Evolution

LINOSPORT XF²

Maintenance instructions

October 2021

EXTRA SPORTIVE USAGE :

USAGE EXTRA SPORTIF						
	Auto Scrubber	Chairs & Tables	Scrubber dryer	Bleachers (with people sitting)	Basketball hoop	Scissor lift
	30kg	80 / 110 kg	max 600 kg	1000kg per leg	1000 kg	max 2T
						
Lumaflex Evolution Linosport xf ²						
		Control the quality of chairs and tables feet.		Minimum surface of a Leg : 25cm ² . Minimum space between legs : 50cm.		Periodical maintenance : 2 times per year.

Caution: Compliance with the point loads given for the bleacher, basketball hoop and scissor lift does not mean that the floorcovering will not be left with a permanent indentation. We recommend the use of contact elements that do not make an indentation (polyurethane white wheels for example), or of distribution plates in the event of doubt.



Polyurethane wheels

Protection of the flooring during non-sportive events

In order to protect the flooring during non-sportive events, like a fair, concert or ball, we recommend the use of Tarkett Sports Protectiles or Touchdown. Under stage or podium, we recommend also to protect floor with distribution plates.

If any doubts, please contact your local Tarkett Sports representative for further information.

