

Specification Model

2020

Excellence Genius

Heterogeneous vinyl loose-lay

ACCZENT EXCELLENCE GENIUS 70

The selected flooring similar to Acczent Excellence 70 belongs to the compact vinyl floors category under ISO standard 10582, available in 2m wide sheet with a Type I binder content.

Acczent Excellence Genius product allows full loose-lay installation (glue-free). The product can be installed on multiple subfloors, especially in case of renovation over existing subfloors, including asbestos*, and on damp subfloors**, thanks to integrated a damp protection layer.

It has a static indentation resistance ≤ 0.01 mm.

The product formulation does not contain phthalate-based plasticizer. It is built on a calandered backing layer made of recycled vinyl flooring material. It contains over 20% recycled material.

The wear layer of 0.70mm is reinforced with a UV photo-crosslinked polyurethane including particles of alumina TopCleanXP™ treatment, which permanently suppresses any wax and regenerating polish spray maintenance operations.

It offers a dimensional stability $\leq 0,04\%$ according to EN ISO 23999 standard. Its gloss rate is $\leq 5\%$ and it can be installed with multicolour welding rods to ensure seamless finish.

TAPIFLEX EXCELLENCE GENIUS 70

The selected flooring similar to Tapiflex Excellence Genius 70 belongs to the acoustic vinyl floors category under EN standard 649, available in 2m wide sheet with a Group T wear rating.

Tapiflex Excellence Genius product allows full loose-lay installation (glue-free). The product can be installed on multiple subfloors, especially in case of renovation over existing subfloors, including asbestos*.

It has an acoustic performance of **19 dB** and a static indentation resistance ≤ 0.10 mm.

✓ 10 years Warranty

✓ Sustainability credentials

- The product is **100 % recyclable**.
- Installation off-cuts and **post-use flooring** can be collected through Tarkett ReStart® program.
- Installation off-cuts and **post-use flooring** can be recycled & used to reproduce high quality products comparable to the original ones.

✓ Optimal Indoor Air Quality

- Very low emissions of VOCs (Volatile Organic Compounds), **$<10\mu\text{g}/\text{m}^3$** , tested 28 days after installation, a threshold 100 times lower than levels set by the most stringent EU regulations. It is free of formaldehyde.

- The selected flooring is covered by a specific third-party verified Environmental Product Declaration (EPD), disclosing among other indicators the carbon footprint of the flooring during its whole lifecycle (production, construction, use and end-of-life).
- The selected flooring is also covered by a third-party verified ingredient disclosure and material risk declaration down to 0.01%, thus ensuring compliance far beyond REACH regulation requirements, such as Material Health. Statement (MHS) delivered by the Environmental Protection Encouragement Agency (EPEA).

* According to local regulations

** Please refer to installation notice

If any doubts or clarifications should be needed, please contact your local Tarkett representative for further information.

